

20050561

TECALAN®-Kunststoffrohr

TR 12,5/10 w nf



30.05.2023 16:19:05

Technical Data

Weight

colour

max. operating pressure (bar)	15
minimum bend radius	75,000 millimeter
nominal size / DN	13 millimeter
outer diameter	12,5
stabilized	not stabilized
wall thickness	1,250 millimeter
Conformity	

47 g per meter

natural

REACH regulation

Commodity code

China-RoHS

Dual-Use

2006/1907/EG (REACH)

RoHS directive

2011/65/EU (RoHS II)

39173200

n/a

no

RoHS directive (III)

2015/863/EC (RoHS III)

Karl Heitz Industrievertretungen GmbH | Senner Straße 151 | D-33659 Bielefeld



^{*} n/s - not specified n/a - not applicable

^{**} technical specifications/ conformities



20050561

TECALAN®-Kunststoffrohr

TR 12,5/10 w nf



This data sheet has been created with great care and all information has been checked for correctness. However, no liability is accepted for any incorrect or incomplete information. Product images and drawings are for illustration purposes only and may vary in detail. Due to the constant further development of the products, changes in the product range and the product design are reserved! Performance and consumption data as well as descriptions may therefore differ. The use of the products is beyond our control and is therefore not our area of responsibility.